

HF Carbon Rev Date: 06/22/09

SAFETY DATA SHEET

SECTION 1. COMPANY IDENTIFICATION AND CHEMICAL PRODUCT

Company Name: Lawrence Factor, Inc.

Address: 4740 NW 157 Street, Miami Lakes, FL 33014

Phone / Fax: 305-430-0550 / 305-430-0864

Chemical Name: HF Carbon

Product Use: Liquid and Vapor Applications (Purification, Decolorization, Separation, and Deodorization)

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

 Identity:
 HF Carbon

 CAS No.:
 7440-44-0

 %:
 100

SECTION 3. HAZARDS IDENTIFICATION

Emergency Overview: Odorless black granules or powder. **HF Carbon (especially when wet) can deplete**

oxygen from air in enclosed spaces, and dangerously low levels of oxygen may result. When workers enter a vessel containing HF Carbon, follow procedures for potentially low oxygen. Workers should also take appropriate precautions when dealing with spent

(used) HF Carbons which may exhibit properties of adsorbed materials.

Potential Health

Effects: Medical conditions aggravated by exposure: None documented

Routes of Exposure

Eyes • Not Corrosive but like most particulate materials, may cause mild physical irritation.

Skin • Not Corrosive and not a primary skin irritant. Mild irritation is possible due to abrasive

action of dust.

Ingestion · No known deleterious effects.

Inhalation Possible mild irritation of respiratory tract due to drying and abrasive actions of dust.

Chronic Effects · IARC: Not Listed · NTP: Not Listed · OSHA: Not Regulated

For additional information, see section 16.

SECTION 4. FIRST AID MEASURES

Skin Wash material off the skin with soap and water. Seek medical attention if irritation occurs.

Eyes · Flush with copious amounts of water. Seek medical attention if irritation occurs.

Ingestion · Give one or two glasses of water to drink. Seek medical attention if gastrointestinal

symptoms develop.

Inhalation Remove to fresh air. Seek medical attention if cough or respiratory symptoms develop.

SECTION 5. FIRE FIGHTING MEASURES

Flashpoint · Not Applicable Non-Flammable · 16CFR1500.44.

Not Self Heating · UN Manual of Tests and Criteria, Test N.3.

Flammability Limits in Air · LFL and UFL Not Applicable.

General Hazard: HF Carbon is difficult to ignite and tends to burn slowly (smolder) without producing

smoke or flame. Toxic gases will form upon combustion.

Fire Fighting Instructions: If possible to do safely, move smoldering HF Carbon to a non-hazardous area,

preferably out of doors. Extinguish fire using water fog, fine water spray, carbon dioxide or

LFI110R1F4 Page | 1 of 5





foam. Avoid stirring up dust clouds.

Fire Fighting Equipment: Fire fighting personnel should wear full protective equipment, including self-contained

breathing apparatus (SCBA) for all inside fires and large outdoor fires.

Hazardous Combustion

Products:

Combustion products may include smoke and oxides of carbon (for example, carbon monoxide). Materials allowed to smolder for long periods in enclosed spaces, may produce amounts of carbon monoxide which reach the lower explosive limit (carbon monoxide LEL = 12.5% in air). Under certain conditions, any airborne dust may be an explosion hazard. Used hf carbon may produce

additional combustion products.

SECTION 6. ACCIDENTAL RELEASE MEASURES

If a Spill or Leak Occurs: Clean up spills in a manner that does not disperse dust into the air. Handle in accordance

with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure, and removal of material from eyes, skin, and clothing.

Disposal Method: Spent granular HF Carbon may be recyclable. Dispose of virgin (unused) carbon

(waste or spillage) in a facility permitted for non-hazardous wastes. Spent (used) carbon

should be disposed of in accordance with applicable laws.

Container Disposal: Do not reuse empty bags. Dispose of in facility permitted for non-hazardous wastes.

SECTION 7. HANDLING AND STORAGE

Storage Temperature Storage Pressure

Handling

AmbientAtmospheric

· Follow good handling and housekeeping practices to minimize spills, generation of

airborne dusts, and accumulation of dusts on exposed surfaces.

· Use with adequate exhaust ventilation to draw away from workers breathing zones.

· Prevent or minimize exposures to dusts by using appropriate personal protection equipment.

· Wash exposed skin areas thoroughly with soap and water after handling.

Storage Store product in a closed dry container. Maintain good housekeeping. Store away from

strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls
Eye Protection

· Use local exhaust ventilation to control emissions near the source.

· Safety glasses with side shields are recommended for any type of handling. Where eye contact or dust conditions may be likely, dust tight goggles are recommended. Have eye

flushing equipment available.

Skin Protection · Avoid skin contact with this product. Wear appropriate dust resistant clothing. Wash contaminated

clothing and clean protective equipment before reuse. Wash skin thoroughly after handling.

Respiratory Protection · Keep dust exposure to a minimum with engineering and administrative controls. Use

appropriate NOISH/MSHA approved particulate respirators if necessary. Observe

respirator use limitations specified by NOISH/MSHA or the manufacturer.

Airborne Exposure Recommended Exposure HF Carbon

Guidelines: <u>Limits 8-hr TWA</u>

Total Dust 7.5 mg/m3*
Respirable Fraction 2.5 mg/m3*

LFI110R1F4 Page | 2 of 5

^{*}OSHA and ACGIH have not established specific exposure limits for this material. These guidelines are based on a conservatively highly concentration of silica quartz (2%). Actual airborne silica concentrations may be much lower. If so, the PEL or TLV would be higher. No ceiling or short-term exposure limits have been set by OSHA or ACGIH.





SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point · NA Freezing Point, C · NA

Bulk Density - Granular Grades · 21-25 lbs/ft3 % Volatiles · NA

Bulk Density - Powder Grades · 15-35 lbs/ft3 Solubility in Water · Insoluble

Vapor Pressure · NA Appearance and Odor · Black granules or Vapor Density · NA powder with no odor

Evaporation Rate · NA

SECTION 10. STABILITY AND REACTIVITY DATA

Stability This product is stable under the specified conditions of storage, shipment and use.

Incompatibility · Contact with strong oxidizers such as ozone, liquid oxygen, chlorine, permanganate, etc.

may result in rapid combustion. Avoid contact with strong acids.

Hazardous

Decomposition Products · Oxides of Carbon Hazardous Polymerization · Does not Occur

SECTION 11. TOXICOLOGICAL INFORMATION

This material is non-toxic in its original state. Used HF Carbon may exhibit

characteristics of the adsorbed material.

SECTION 12. ECOLOGICAL INFORMATION

This material, in its original state, is not harmful to the environment. Used HF Carbon

may exhibit characteristics of the adsorbed material.

SECTION 13. DISPOSAL CONSIDERATIONS

 \cdot HF Carbon, in its original state, is not a hazardous material or hazardous waste.

· Follow applicable governmental regulations for waste disposal.

· Used HF carbon may become classified as a hazardous waste depending upon the application.

· Follow applicable regulations for disposal.

· Recycling (reactivation) may be a viable alternative to disposal.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation)

Proper Shipping Name · HF Carbon (Not DOT Regulated)

Hazard Class · NA
UN/NA Number · NA
Packing Group · NA

Freight Classification · STCC Code - #2899643 NMFC #040560

SECTION 15. REGULATORY INFORMATION

Federal Regulations:

OSHA Hazard See "Particulates not otherwise regulated", in Table Z-1 Communication of 29CFR1910.1000, "Limits For Air Contaminates".

Standard,

29CFR1910.1200:

 ${\tt CERCLA/SUPERFUND,} \qquad \cdot \ {\tt Notification\ of\ spills\ of\ this\ material\ is\ not\ required.}$

40CFR117,302:

LFI110R1F4 Page | 3 of 5

^{*}NA - Not Applicable

^{*}NA - Not Applicable





SARA/SUPERFUND

- · Section 302- Extremely Hazardous Substances (40CFR355): This product is not listed as an extremely hazardous substance.
- · Section 313 List of Toxic Chemicals: This product is not listed.

Toxic Substances Control Act, 40CFR710 · HF Carbon is on the inventory list.

Resource Conservation & Recovery Act

· HF Carbon, in its original state, does not meet the criteria of hazardous waste.

State Regulations:

California Occupational
Safety & Health

· Not Listed

Massachusetts Substance List · Not Listed

New Jersey Right-to-Know · Not Listed

Pennsylvania Right-to-Know Not Listed

SECTION 16.

OTHER INFORMATION

HF Carbon can be safely stored in any normal storage area, but away from sources of direct heat.

References:

Not Available

Other Considerations:

WARNING: HF Carbon (especially when wet) can deplete oxygen from the air, and dangerously low levels of oxygen may result. When workers enter a vessel containing hf carbon, procedures for potentially low oxygen areas should be followed.

HF Carbons are not listed as potential carcinogens by any agency. HF Carbon may contain crystalline silica, which has been listed as a potential carcinogen of the lungs by the International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP). Much of the silica is inextricably bound within the particles of HF carbon, and does not present a substantial health hazard. Because Lawrence Factor, Inc adheres to a very conservative position regarding all health and safety matters, we recommend and follow a practice of requiring respiratory protection whenever there is any evidence of airborne dust.

Product emergencies:

If you have a product-related emergency, resulting in an accident such as a spill or release of product or human exposure and need assistance from Lawrence Factor, please contact the following number: LAWRENCE FACTOR, INC. 1-800-338-5493 or 305-430-0550

LFI110R1F4 Page | 4 of 5





General:

The data and recommendations presented in this data sheet concerning the use of our product and the materials contained therein are believed to be accurate and are based on information which is considered reliable as of the date hereof. However, the customer should determine the suitability of such materials for his purpose before adopting them on a commercial scale. Since the use of our products by others is beyond our control, no guarantee, express or implied, is made and no responsibility assumed for the use of this material or the results to be obtained there from. Information on this form is furnished for the purpose of compliance with Government Health and Safety Regulations and shall not be used for any other purposes. Moreover, the recommendations contained in this data sheet are not to be construed as a license to operate under, or a recommendation to infringe, any existing patents, nor should they be confused with state, municipal or insurance requirements, or with national safety codes.

This information is furnished without warranty expressed or implied, except that it is accurate to the best knowledge of Lawrence Factor, Inc. The data on this sheet related only to the specific material designed herein. Lawrence Factor, Inc. assumes no legal responsibility for the use or reliance upon these data.

LFI110R1F4 Page | 5 of 5